Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-6273

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

1.562 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.750 inches

#### Body Length:

1.375 inches

#### Overall Diameter:

1.719 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Nonturn Device Location:

At 6 oclock

### Nonturn Device Radius:

0.500 inches

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Locking bushing

## **Electrical Resistance Per Section:**

5.0 kilohms single section

## Power Dissipation Rating Per Section In Watts:

25.0 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section



### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

### Standard Taper Curve Per Section:

A single section

**Special Features:** 

200.0 degrees c at 46 per cent rated power

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0