Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-6370

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# Body Diameter:

1.280 inches

## Shaft Diameter:

0.250 inches

#### Shaft Length:

0.875 inches

## Mounting Bushing Length:

0.375 inches

## Body Length:

0.625 inches

#### Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

1.000 kilohms single section

## **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Standard Taper Curve Per Section:

A single section

## **Test Data Document:**

81349-mil-r-19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

3 tab, solder lug

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0