NSN 5905-00-108-8463

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-8463

Section Quantity:						
1						
Body Style:						
Cylindrical bushing mounted						
Reliability Indicator:						
Not established						
Overall Length:						
1.406 inches						
Body Diameter:						
1.656 inches						
Shaft Diameter:						
0.250 inches						
Shaft Length:						
0.625 inches						
Mounting Bushing Length:						
0.500 inches						
Body Length:						
0.781 inches						
Shaft Style:						
Round, slotted						
Actuator Type:						
Single shaft						
Nonturn Device Location:						
At 9 oclock						
Nonturn Device Radius:						
0.531 inches						
Screw Thread Diameter:						
0.375 inches						
Screw Thread Series Designator:						
Unef						
Screw Thready Qty Per Inch (tpi):						
32.0						
Terminal Location:						
Radially positioned over less than half the circumference						
Mounting Method:						
Standard bushing						
Features Provided:						
Shaft locking device						
Electrical Resistance Per Section:						
25.0 kilohms single section						
Power Dissipation Rating Per Section In Watts:						

3.0 free air single section

NSN 5905-00-108-8463

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



R	esistance	Tolerance	Per 9	Section	In	Percent:
◥	esisiance	i olei alice	rei .	Section		reiteiit.

-10.0 to 10.0 single section

Terminal Type And Quantity:

3 tab, solder lug

.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0