## NSN 5905-00-108-8521

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-8521 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.312 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.875 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 290.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally closed **Screw Thread Diameter:** 0.500 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 28.0

Terminal Location:

Rear-bottom

## NSN 5905-00-108-8521

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
500.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
290.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
2.000 ac
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0