Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-8581

Section Quantity:

1

Body Style:

Cylindrical studs mounted

Reliability Indicator:

Not established

Body Diameter:

5.250 inches

Shaft Diameter:

0.375 inches

Shaft Length:

1.250 inches

Body Length:

2.562 inches

Mounting Hole/stud Circle Diameter:

2.125 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Screw Thread Diameter:

0.164 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

100.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

25.0 free air single section



Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0