Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-8585

# Section Quantity:

1

Body Style:

Cylindrical studs mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

3.000 inches

### Shaft Diameter:

0.375 inches

### Shaft Length:

0.938 inches

Body Length:

2.625 inches

### Mounting Hole/stud Circle Diameter:

# 0.875 inches

Shaft Style:

Round

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

## Screw Thread Diameter:

0.164 inches

## Screw Thread Series Designator:

Unc

## Screw Thready Qty Per Inch (tpi):

32.0

# Mounting Facility Quantity:

3

## **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Threaded hole

## **Electrical Resistance Per Section:**

200.0 kilohms single section

## **Rotary Actuator Travel In Angular Deg:**

300.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# Power Dissipation Rating Per Section In Watts:

12.0 free air single section



## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

### **Actuator Travel Control Feature:**

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0