NSN 5905-00-108-8592

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-8592

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.187 inches
Terminal Length:
0.531 inches
First Flat Length:
0.250 inches
Flat Height:
0.188 inches
Body Diameter:
Between 0.656 inches and 0.781 inches
Shaft Diameter:
Between 0.248 inches and 0.250 inches
Shaft Length:
0.625 inches
Body Length:
Between 0.500 inches and 0.625 inches
liidiameter:
1.219 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.500 megohms single section
Power Dissipation Rating Per Section In Watts:

2.0 free air single section

NSN 5905-00-108-8592

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Special Features:
0.250 inch long bushing

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

No

Fiig:

A002a0