Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-108-9620

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.062 inches

#### Body Diameter:

1.062 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.125 inches

#### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

0.562 inches

#### Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Nonturn Device Location:

At 3 oclock and at 9 oclock

## Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

500.000 ohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

AeroBase Group

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0