## NSN 5905-00-110-0940

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-110-0940

Electrical Resistance: 3.200 kilohms Resistance Tolerance In Percent: -0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Akala terminals one end Test Data Document: 91349-mil/93 specification (includes engineering type builetins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Sheff Life: N/a Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent:  -0.100 to 0.100 Ambient Tempurature in Deg Celsius At Full Rated Power:  125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power:  145.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius:  -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type:  Wire lead Reliability Indicator: Not established Body Diameter: -0.250 inches Body Length: -0.312 inches Power Dissipation Rating in Watts: -0.125 free air  Style Designator: Akalla terminals one end Test Data Document:  81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', "average", "", etc.)  Shelf Life:	-20.0 to 20.0
Resistance Tolerance In Percent: -0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: -0.250 inches Body Length: -0.312 inches Power Dissipation Rating In Watts: -0.125 free air Style Designator: Avial terminals one end Test Data Document: -0.148 psecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: No Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Akial terminals one end Test Data Document: 81349-mile3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Unit Of Measure:	3.200 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  45.0 to 145.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminals one end  Test Data Document:  833-9-milip3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life:  No  Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  165.0 to 145.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead Reliability Indicator:  Not established Body Diameter:  0. 250 inches Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminals one end  Test Data Document:  191349-milir93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  No  Unit Of Measure:	-0.100 to 0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0 to 145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminals one end  Tests Data Document:  81349-mility3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  No  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terrinal Type: Wife lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  165.0 to 145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminals one end  Test Data Document:  81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Test Data Document: B1349-milit93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/A Unit Of Measure: Demilitarization: No Filg:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Rediability Indicator: Not established Body Diameter: 0,250 inches Body Length: 0,312 inches Power Dissipation Rating In Watts: 0,125 free air Style Designator: Axial terminals one end Test Data Document: B1349-miliP3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminals one end  Test Data Document:  B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	-65.0 to 145.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminals one end  Test Data Document:  81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.250 inches  Body Length: 0.312 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminals one end  Test Data Document:  B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Filg:	Encapsulated
Reliability Indicator:  Note stablished  Body Diameter:  0.250 inches  Body Length: 0.312 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminals one end  Test Data Document:  81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Terminal Type:
Note stablished  Body Diameter:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminals one end  Test Data Document:  B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Wire lead
Body Diameter:  0.250 inches  Body Length: 0.312 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminals one end  Test Data Document:  81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Reliability Indicator:
Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminals one end  Test Data Document:  81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Not established
Body Length: 0.312 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Axial terminals one end  Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig:	Body Diameter:
D.312 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminals one end  Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	0.250 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
Style Designator:  Axial terminals one end  Test Data Document:  81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	0.312 inches
Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminals one end  Test Data Document:  81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	0.125 free air
Test Data Document:  81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Style Designator:
B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Axial terminals one end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: Demilitarization: No Filig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
4001a0	Fiig:
	A001a0