

View Online at <https://aerobasegroup.com/nsn/5905-00-110-5103>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

Between 1.470 inches and 1.510 inches

Terminal Length:

0.188 inches

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.2495 inches and 0.2498 inches

Shaft Length:

0.752 inches

Mounting Bushing Length:

0.252 inches

Body Length:

Between 0.658 inches and 0.698 inches

Overall Diameter:

1.063 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 1800.0 and 1810.0

Maximum Starting Torque:

0.60 inch-ounces

Maximum Running Torque:

0.60 inch-ounces

Maximum Stop Torque:

48.00 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.002 inches

Shaft Radial Play:

0.002 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

25.000 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 1800.0 and 1810.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-3.0 to 3.0 single section

Actuator Travel Control Feature:

Stops

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0