NSN 5905-00-110-5133

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-110-5133 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.688 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:**

0.250 inches

Body Length: 0.365 inches **Shaft Style:**

Round, slotted **Actuator Type:**

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

250.0

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

0.312 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

NSN 5905-00-110-5133

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No