NSN 5905-00-110-5137

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-110-5137

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| 0.516 inches |
| Shaft Diameter: |
| 0.125 inches |
| Shaft Length: |
| 0.500 inches |
| Mounting Bushing Length: |
| 0.250 inches |
| Body Length: |
| 0.469 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 295.0 |
| Nonturn Device Location: |
| At 6 oclock |
| Nonturn Device Radius: |
| 0.245 inches |
| Screw Thread Diameter: |
| 0.250 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 500.0 ohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 295.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |

120.0 single section

NSN 5905-00-110-5137

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Power Dissipation Rating Per Section In Watts: |
|---|
| 0.5 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0 to 10.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |