NSN 5905-00-110-7738

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-110-7738 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.785 inches **Body Length:** 0.453 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 270.0 **Maximum Starting Torque:** 4.00 inch-ounces **Maximum Running Torque:** 4.00 inch-ounces **Terminal Location:** Rear end **Mounting Method:** Tab and terminal **Electrical Resistance Per Section:** 200.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 270.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:**

Standard Taper Curve Per Se
A single section
Terminal Type And Quantity:
3 tab, solder lug

NSN 5905-00-110-7738

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Sneit Lite:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0