Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-111-8378

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.719 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.000 inches

Mounting Bushing Length:

#### 0.375 inches

Body Length:

#### 0.812 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

# Features Provided:

Hermetically sealed

# **Electrical Resistance Per Section:**

500.0 ohms single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# Power Dissipation Rating Per Section In Watts:

4.0 free air single section



**Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0