Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-112-3277

Section	Quantity:
---------	-----------

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

#### **Terminal Length:**

0.260 inches

Body Diameter:

0.785 inches

**Body Length:** 

0.422 inches

Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

240.0

Center To Center Distance Between Terminals:

0.770 inches

**Terminal Location:** 

Front end

### **Mounting Method:**

Tab

**Electrical Resistance Per Section:** 

300.0 ohms single section

### **Rotary Actuator Travel In Angular Deg:**

240.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.385 inches

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

# Power Dissipation Rating Per Section In Watts:

1.250 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

### Standard Taper Curve Per Section:

A single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0