Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-112-4461

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## Reliability Indicator:

Not established

## **Terminal Length:**

0.157 inches

### **Body Diameter:**

1.562 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

1.375 inches

### **Overall Diameter:**

1.719 inches

### Shaft Style:

Round

### Actuator Type:

Single shaft

## Nonturn Device Location:

At 6 oclock

### **Nonturn Device Radius:**

0.500 inches

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

350.0 ohms single section

# Power Dissipation Rating Per Section In Watts:

25.0 free air single section



**Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0