NSN 5905-00-112-4491

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-112-4491

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.375 inches
First Flat Length:
1.562 inches
Flat Height:
0.344 inches
Body Diameter:
6.000 inches
Shaft Diameter:
0.375 inches
Shaft Length:
2.000 inches
Body Length:
2.375 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Distance Between Mounting Hole Centers:
2.375 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
20.0
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
400.000 ohms single section
Power Dissipation Rating Per Section In Watts:
300.0 free air single section

NSN 5905-00-112-4491

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab solder lug

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0