NSN 5905-00-112-4518

Fiig: A001a0

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-112-4518

Tempurature Comments of Resistance in Ppin Per Deg Celsius: 22.00 /r/20.0 Electrical Resistance: 33.20.0 ohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Langthe: 0.500 inches Rody Diameter: 0.500 inches Power Dissipation Rating in Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 3134-mill-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as 'typical', "average*, ", etc.). Specification Data: \$1349-mill-9315 government specification Shelt Life:	Townwature Coefficient Of Resistance In Daw Box Coleives
Electrical Resistance: 33.200 ohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0 to 145.0 Inclosure Method: -65.0 to 145.0 Inclosure Method: -67.0 to 145.0 Inclosure Meth	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Full Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0 to 145.0 Tempia Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0 to 145.0 Tempia Temp	
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mili-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mili-93/15 government specification	
-1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: -73.b, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mill-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mill-r-93/15 government specification	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.590 inches Body Diameter: 0.590 inches Body Length: 0.590 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mill-r-93/15 government specification bata: 81349-mill-r-93/15 government specification bata: 81349-mill-r-93/15 government specification in Data County in Carte County in Carte Carte County in Carte County in Carte Carte County in Carte Carte County in Carte Cart	
125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliablity Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 1349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-93/15 government specification	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Reliability Indicator such as a sold irreliable such as a sold	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating in Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil93/15 government specification	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-65.0 to 145.0 inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	145.0
Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	-65.0 to 145.0
Taminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Inclosure Method:
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Encapsulated
Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Terminal Type:
Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Tab, solder lug
Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Reliability Indicator:
Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Not established
Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Terminal Length:
Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	0.375 inches
Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Body Diameter:
O.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	0.500 inches
Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Body Length:
0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	0.500 inches
Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Power Dissipation Rating In Watts:
0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	0.250 free air
Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Terminal Width:
Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	0.188 inches
Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Style Designator:
81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Radial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-93/15 government specification	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Specification Data: 81349-mil-r-93/15 government specification	
	Specification Data:
	81349-mil-r-93/15 government specification
N/a	N/a
Unit Of Measure:	Unit Of Measure:
<u></u>	<u></u>
Demilitarization:	Demilitarization:
No	No