## NSN 5905-00-112-4533

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-112-4533

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.625 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.714 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.562 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
275.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
294.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:

3.0 free air single section

## NSN 5905-00-112-4533

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A002a0