NSN 5905-00-113-0381

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-113-0381

Section Quantity:

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.470 inches
Overall Height:
0.320 inches
Overall Width:
0.190 inches
Mounting Hole Diameter:
0.088 inches
Shaft Diameter:
0.110 inches
Shaft Length:
0.070 inches
Body Length:
1.250 inches
Body Width:
0.190 inches
Body Height:
0.320 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7920.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2

Terminal Location:

Rear end

NSN 5905-00-113-0381

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
40.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0