NSN 5905-00-113-1292

Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-113-1292

-30.0 to 30.0 to 30.0 to 20.0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.8695 to 1.8695 Ambient Tempurature In Deg Celsius At Full Rated Power: 66.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.800 free air Style Designator: Availateminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	-30.0 to 30.0
Resistance Tolerance In Percent: -1.8695 to 1.8695 Ambient Tempurature In Deg Celsius At Full Rated Power: 66.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wrire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-84 16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Electrical Resistance:
-1.8695 to 1.9695 Ambient Tempurature In Deg Celsius At Full Rated Power: 66.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Sylve Designator: Axial terminal each end Test Data Document: 64.959-8416764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	2.300 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 66.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 425.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Avial terminal each end Test Data Document: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig:	Resistance Tolerance In Percent:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.800 free air Style Designator: Axial terminal each end Test Data Document: 64959-kst 16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Na Unit Of Measure:	-1.8695 to 1.8695
Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.750 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
+25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.800 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Flig:	66.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.750 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", **, etc.). Sheft Life: Na Unit Of Measure: Demilitarization: No Fiig:	+25.0 to 85.0
Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure: Demilitarization: No Filg:	Inclosure Method:
Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Terminal Type:
Inductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reactance Characteristic:
Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inductive
Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not established
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.375 inches
Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
O.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.750 inches
Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.600 free air
Test Data Document: 64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	64959-ks16764 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0