NSN 5905-00-113-3557

Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-113-3557

Electrical Resistance: 37.100 ohms Resistance Tolerance in Percent: 0.153 to 0.153 Ambient Tempurature In Deg Celsius At Full Rated Power: 36.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 125.0 to 85.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Resistance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Diameter: 0.500 free air Style Designator: Avial terminal each end Test Data Document: Style Designator: Avial terminal each end Test Data Document: Shelf-Life: Wire Unit Of Measure: — Demilitarization: No Demilitarization: No Demilitarization: No Demilitarization: No Demilitarization:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: 0.153 to 0.153 Ambient Tempurature in Deg Celsius At Full Rated Power: 38.0 Fempurature Range Of Tempurature Coefficient in Deg Celsius: +25.0 to 85.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established 38.0dy Diameter: 0.375 inches 38.0dy Length: 0.750 inches Power Dissipation Rating in Watts: 0.600 free air Style Designator: Avial terminal each end Fest Data Document: Style Test Toron On the Advancing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure:	-30.0 to 30.0
Resistance Tolerance In Percent: 0.153 to 0.153 Ambient Tempurature In Deg Celsius At Full Rated Power: 8.6.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1.25.0 to 85.0 Inclosure Method: 1.0153 to 0.153 Inclosure Method: 1.0153 to 0.153 Inclosure Method: 1.0154 to 0.1555 Inclosure Method: 1.0155 to 0.1555 Inclosure Method: In	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 36.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 425.0 to 85.0 noclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Realiability Indicator: Not established 30dy Diameter: 3.375 inches Body Length: 2.750 inches Power Dissipation Rating in Watts: 2.0600 free air Style Designator: 4xial terminal each end Test Data Document: 534959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Juit Of Measure: — Demilitarization: No Filig:	37.100 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 36.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 425.0 to 85.0 Inclosure Method: 5.0.00 recopsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 3.375 inches Body Length: 9.050 inches Power Dissipation Rating In Watts: 9.060 free air Style Designator: Awaid terminal each end Tests Data Document: 934959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: 5.0.00 fineasure: 5.0.00 fi	Resistance Tolerance In Percent:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 125.0 to 85.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 3.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 6.600 free air Style Designator: Akial terminal each end Fest Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure:	-0.153 to 0.153
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 125.0 to 85.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Fest Data Document: 84959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wia Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
inclosure Method: Encapsulated Ferminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.400 free air Style Designator: Axial terminal each end Fest Data Document: 94959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wie Unit Of Measure:	66.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Baddy Diameter: 0.375 inches Baddy Length: 0.750 inches Power Dissipation Rating In Watts: 0.800 free air Style Designator: Avail terminal each end Fest Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating in Watts: 0.600 free air Style Designator: Avial terminal each end Test Data Document: 64959-ks 16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wia Unit Of Measure: Demilitarization: No Filig:	+25.0 to 85.0
Ferminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 3.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Avial terminal each end Test Data Document: 34959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Filig:	Inclosure Method:
Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Skyle Designator: Axial terminal each end Fest Data Document: 34959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: Demilitarization: No Filig:	Encapsulated
Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Fest Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Terminal Type:
Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Fest Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Wire lead
Reliability Indicator: Note established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Fest Data Document: 84959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Reactance Characteristic:
Note established Body Diameter: D.375 inches Body Length: D.750 inches Power Dissipation Rating In Watts: D.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Noninductive
Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Unit Of Measure: Demilitarization: No	Reliability Indicator:
D.375 inches Body Length: D.750 inches Power Dissipation Rating In Watts: D.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Unit Of Measure: Demilitarization: No	Not established
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Body Diameter:
Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.375 inches
Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 0.4959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Body Length:
O.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.750 inches
Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: V/a Unit Of Measure: Demilitarization: No Filig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.600 free air
Fest Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Style Designator:
64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Filig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Fiig:	Demilitarization:
	No
\ 001a0	Fiig:
	A001a0