NSN 5905-00-113-3570

Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-113-3570

-30.0 to 30.0 to 30.0 to 20.0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -0.1256 to 0.1256 Ambient Tempurature in Deg Celsius At Full Rated Power: 66.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: +25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating in Watts: 0.800 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	-30.0 to 30.0
Resistance Tolerance in Percent: -0.1256 to 0.1256 Ambient Tempurature in Deg Celsius At Full Rated Power: 66.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Note established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating in Watts: 0.800 free air Style Designator: Axial terminal each end Test Data Document: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit Of Measure:	Electrical Resistance:
-0.1256 to 0.1256 Ambient Tempurature In Deg Celsius At Full Rated Power: 66.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 84059-8416764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	78.100 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 66.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-8x16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Resistance Tolerance In Percent:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: +25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-0.1256 to 0.1256
Tempurature Range Of Tempurature Coefficient in Deg Celsius: +25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.800 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
#25.0 to 85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	66.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks 16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	+25.0 to 85.0
Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Inclosure Method:
Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reactance Characteristic: Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Noninductive Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reactance Characteristic:
Note established Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc., excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Noninductive
Body Diameter: 0.375 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not established
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
0.750 inches Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.375 inches
Power Dissipation Rating In Watts: 0.600 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.750 inches
Style Designator: Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.600 free air
Test Data Document: 64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc., excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	64959-ks16764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0