Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-113-4901

| Section | Quantity: |
|---------|-----------|

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.500 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.040 inches

Body Length:

1.060 inches

Body Width:

# 0.312 inches

**Body Height:** 

0.355 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

**Center To Center Distance Between Terminals:** 

0.700 inches

**Terminal Location:** 

Rear end

**Mounting Method:** 

Terminal

**Electrical Resistance Per Section:** 

200.0 ohms single section

#### **Rotary Actuator Travel In Angular Deg:**

3600.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.400 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section



### **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

## Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0