

View Online at <https://aerobasegroup.com/nsn/5905-00-113-8265>

**Section Quantity:**

1

**Body Style:**

Cylindrical

**Reliability Indicator:**

Not established

**Terminal Length:**

0.300 inches

**Body Diameter:**

Between 0.490 inches and 0.510 inches

**Body Length:**

Between 0.225 inches and 0.245 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

315.0

**Center To Center Distance Between Terminals:**

0.200 inches

**End Application:**

Los angeles class ss (688), sturgeon class ssn(637), communications terminal satellite an/gsc-39(v)1, general purpose electronic test equipment, virginia class cgn(41), emory s.Land class as, iwo jima class lph, missile allweather antiship harpoon(agm-84) , oliver perry class ffg, nimitz class cvn

**Terminal Location:**

Rear end

**Mounting Method:**

Terminal

**Electrical Resistance Per Section:**

20.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

320.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.100 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

**Actuator Travel Control Feature:**

Stops

**Criticality Code Justification:**

Feat

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0