

View Online at <https://aerobasegroup.com/nsn/5905-00-113-8265>

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Terminal Length:

0.300 inches

Body Diameter:

Between 0.490 inches and 0.510 inches

Body Length:

Between 0.225 inches and 0.245 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

315.0

Center To Center Distance Between Terminals:

0.200 inches

End Application:

Los angeles class ss (688), sturgeon class ssn(637), communications terminal satellite an/gsc-39(v)1, general purpose electronic test equipment, virginia class cgn(41), emory s.Land class as, iwo jima class lph, missile allweather antiship harpoon(agm-84) , oliver perry class ffg, nimitz class cvn

Terminal Location:

Rear end

Mounting Method:

Terminal

Electrical Resistance Per Section:

20.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

320.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops

Criticality Code Justification:

Feat

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Weapon system essential

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0