NSN 5905-00-114-3183

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-114-3183

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.438 inches
Body Diameter:
1.250 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.563 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Special Features:
Spiral spring connector
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a

NSN 5905-00-114-3183

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0