NSN 5905-00-114-3349

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-114-3349

Out to Out to
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Terminal Length:
0.340 inches
Body Diameter:
1.062 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.562 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
2.500 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

NSN 5905-00-114-3349

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0