NSN 5905-00-114-4573

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-114-4573

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
0.906 inches
Body Diameter:
1.250 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.760 inches
Overall Diameter:
1.125 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
555.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
2.0 kilohms single section
Function Conformity Tolerance Per Section:

-0.25 to 0.25 single section

NSN 5905-00-114-4573

Precision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 100.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0 to 3.0 single section **Function Characteristic Per Section:** Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity: 3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0