NSN 5905-00-114-4578

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-114-4578 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 0.906 inches **Body Diameter:** 1.250 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.760 inches **Overall Diameter:** 1.250 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 555.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:**

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

500.0 ohms single section

Rotary Actuator Travel In Angular Deg:

555.0

NSN 5905-00-114-4578

No Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Conformity Tolerance Per Section: -0.50/+0.50 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 100.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** Demilitarization: