Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-114-5443

#### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.250 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

#### Body Length:

### 0.562 inches

Shaft Style:

Round

### Actuator Type:

Single shaft

### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.531 inches

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Lower adjacent side single row

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

50.0 kilohms single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## **Special Features:**

Has a spiral spring connector



## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A002a0