NSN 5905-00-114-8068

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-114-8068

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.187 inches
Body Diameter:
1.125 inches
Shaft Diameter:
Between 0.248 inches and 0.250 inches
Shaft Length:
Between 0.609 inches and 0.641 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.562 inches
Overall Diameter:
1.437 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock
Nonturn Device Radius:
Between 0.515 inches and 0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
250.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section

NSN 5905-00-114-8068

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0