NSN 5905-00-114-8780

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-114-8780

Out to Out to
Section Quantity:
1
Reliability Indicator:
Not established
First Flat Length:
0.375 inches
Flat Height:
0.216 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Shaft Style:
Round, flatted
Switch Voltage Rating In Volts:
117.0
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 ohms single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
4.0 free air single section Resistance Tolerance Per Section In Percent:
· · · · · · · · · · · · · · · · · · ·

5 tab, solder lug

NSN 5905-00-114-8780

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0