NSN 5905-00-114-8798

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-114-8798

Section Quantity:
Section Quantity:
·
Body Style: Cylindrical bushing mounted
•
Reliability Indicator: Not established
First Flat Length: 0.344 inches
Flat Height:
0.219 inches
Body Diameter:
1.562 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.375 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 ohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

NSN 5905-00-114-8798

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power	Dissi	pation	Rating	Per	Section	In	Watts:
-------	-------	--------	--------	-----	----------------	----	--------

25.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0