Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-114-9797

Section Quantity:

1

**Reliability Indicator:** 

Not established

First Flat Length:

0.344 inches

Flat Height:

0.219 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

## Nonturn Device Location:

At 3 oclock and at 6 oclock and at 9 oclock and at 12 oclock

**Nonturn Device Radius:** 

0.500 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

**Electrical Resistance Per Section:** 

250.000 ohms single section

**Power Dissipation Rating Per Section In Watts:** 

25.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

## NSN 5905-00-114-9797

Nonprecision Wire Wound Variable Resistor - Page 2 of 2

**Fiig:** A002a0

