Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-114-9869

#### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.484 inches

#### Body Diameter:

1.781 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

#### Mounting Bushing Length:

### 0.375 inches

**Body Length:** 

0.984 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

3.500 kilohms single section

# Power Dissipation Rating Per Section In Watts:

4.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Terminal Type And Quantity:

3 tab, solder lug

# NSN 5905-00-114-9869

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0