NSN 5905-00-115-2001

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-115-2001

Section Quantity:
1
Shaft Diameter:
0.250 inches
Shaft Length:
0.562 inches
Shaft Style:
Round, cross slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
352.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.30 inch-ounces
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50 to 0.50 single section
Power Dissipation Rating Per Section In Watts:
2.75 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0 to 1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-3.0 to 3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-115-2001

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
4 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0