Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-115-3572

Secti	on Quantity:
1	on quantity.
	Style:
Cylind	-
•	bility Indicator:
	stablished
	inal Length:
	inches
-	Diameter:
-	inches
	Length:
-	inches
	ator Type:
	drive with slot-hole
	tive Electrical Rotation In Deg Angular Rotation:
320.0	
Cente	er To Center Distance Between Terminals:
0.200	inches
Term	inal Location:
Rear	end
Mour	ting Method:
Termi	-
Featu	ires Provided:
Herm	etically sealed
	rical Resistance Per Section:
25.0 ł	kilohms single section
	y Actuator Travel In Angular Deg:
360.0	
Cente	er To Center Distance Between Center Terminal And Outside Terminal:
0.100	inches
Ambi	ent Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
	single section
	ourature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-	to 50.0 single section
	er Dissipation Rating Per Section In Watts:
	ree air single section
	stance Tolerance Per Section In Percent:
-5.0 to	o 5.0 single section
	ator Travel Control Feature:
	nuous motion
	ent Tempurature In Deg Celsius Per Section At Full Rated Power:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0