

View Online at <https://aerobasegroup.com/nsn/5905-00-115-5359>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.750 inches

Terminal Length:

0.390 inches

Body Diameter:

Between 1.031 inches and 1.188 inches

Shaft Diameter:

Between 0.125 inches and 0.250 inches

Shaft Length:

Between 0.750 inches and 1.125 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.312 inches

Body Inside Diameter:

Any acceptable

Overall Diameter:

1.484 inches

Shaft Style:

Round

Actuator Type:

Dual concentric

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

50.000 ohms 1st section

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 2nd section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0