

View Online at <https://aerobasegroup.com/nsn/5905-00-115-8080>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

0.875 inches

**Shaft Diameter:**

Between 0.1245 inches and 0.125 inches

**Shaft Length:**

Between 0.670 inches and 0.710 inches

**Mounting Bushing Length:**

Between 0.245 inches and 0.260 inches

**Body Length:**

0.755 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

324.0

**Maximum Starting Torque:**

1.75 inch-ounces

**Maximum Running Torque:**

1.75 inch-ounces

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

0.312 inches

**Shaft End Play:**

0.006 inches

**Shaft Radial Play:**

0.003 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

22.275 kilohms 2nd section

**Rotary Actuator Travel In Angular Deg:**

345.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.0 free air all sections

**Function Conformity Per Section:**

All sections independent linearity

**Resistance Tolerance Per Section In Percent:**

-0.5 to 0.5 1st section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0