

View Online at <https://aerobasegroup.com/nsn/5905-00-116-1157>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.62400 inches and 0.62500 inches

Pilot Length:

0.06200 inches

Overall Length:

Between 1.943 inches and 1.955 inches

Terminal Length:

0.188 inches

Undercut Diameter:

Between 0.780 inches and 0.786 inches

Undercut Width:

0.06300 inches

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

0.375 inches

Body Length:

Between 1.568 inches and 1.580 inches

Overall Diameter:

1.063 inches

Mounting Lip Diameter:

0.87500 inches

Mounting Lip Depth:

0.06200 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 3600.0 and 3610.0

Maximum Starting Torque:

0.60 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.00300 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 3600.0 and 3610.0

Function Conformity Tolerance Per Section:

-0.05/+0.05 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-0.0/+130.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0