NSN 5905-00-116-2382

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-116-2382

Section Quantity: 1 Body Style: Rectangular Reliability Indicator: Not established Terminal Length: 0.300 inches Shaft Diameter: 0.090 inches Shaft Length: 0.040 inches Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0 Center To Center Distance Between Terminals:
Body Style: Rectangular Reliability Indicator: Not established Terminal Length: 0.300 inches Shaft Diameter: 0.090 inches Shaft Length: 0.040 inches Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Rectangular Reliability Indicator: Not established Terminal Length: 0.300 inches Shaft Diameter: 0.090 inches Shaft Length: 0.040 inches Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Reliability Indicator: Not established Terminal Length: 0.300 inches Shaft Diameter: 0.090 inches Shaft Length: 0.040 inches Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Not established Terminal Length: 0.300 inches Shaft Diameter: 0.090 inches Shaft Length: 0.040 inches Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Terminal Length: 0.300 inches Shaft Diameter: 0.090 inches Shaft Length: 0.040 inches Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Shaft Diameter: 0.090 inches Shaft Length: 0.040 inches Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Shaft Diameter: 0.090 inches Shaft Length: 0.040 inches Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
0.090 inches Shaft Length: 0.040 inches Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Shaft Length: 0.040 inches Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
0.040 inches Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Body Length: 0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
0.375 inches Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Body Width: 0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
0.203 inches Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Body Height: 0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
0.375 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
Effective Electrical Rotation In Deg Angular Rotation: 9000.0
9000.0
Center 10 Center distance between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
500.0 ohms single section
•
Rotary Actuator Travel In Angular Deg: 9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section

NSN 5905-00-116-2382

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: