NSN 5905-00-116-8673

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-116-8673 **Section Quantity: Body Style:** Cylindrical tab/flange mounted **Reliability Indicator:** Not established **Body Diameter:** 0.783 inches **Mounting Hole Diameter:** 0.136 inches **Body Length:** 0.453 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 270.0 **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 200.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 270.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section

Terminal Type And Quantity:

3 tab, solder lug

NSN 5905-00-116-8673

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A002a0