## NSN 5905-00-117-0037

**Section Quantity:** 

Cylindrical bushing mounted

Reliability Indicator:

Not established **Body Diameter:**1.125 inches **Shaft Diameter:**0.250 inches

**Body Style:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-117-0037

Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.500 inches
Undercut Diameter:
0.240 inches
Shaft Style:
Round, undercut
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Undercut Length:
0.094 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section

## NSN 5905-00-117-0037

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0