NSN 5905-00-117-0237



Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-117-0237 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.250 inches First Flat Length: 0.344 inches Flat Height: 0.219 inches **Body Diameter:** 1.562 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 0.844 inches and 0.906 inches **Mounting Bushing Length:** 0.375 inches

Body Length: 1.375 inches

Overall Diameter: 1.719 inches

Shaft Style: Round, flatted

Contact Arm Electrical Off Position:

Fully ccw

Actuator Type:

Single shaft

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.500 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

NSN 5905-00-117-0237

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.000 ohms single section
Power Dissipation Rating Per Section In Watts:
25.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0