NSN 5905-00-117-4693

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-117-4693 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.080 inches First Flat Length: 0.190 inches Flat Height: 0.109 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.268 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 354.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Nonturn Device Location:** At 11: 00 oclock **Nonturn Device Radius:** 0.312 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:**

Unef

NSN 5905-00-117-4693

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
20.0 percent, rated amperes c and better finish
Rotary Actuator Travel In Angular Deg:
354.0
Function Conformity Tolerance Per Section:
0.50 to 0.50 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
35.0 all sections
Power Dissipation Rating Per Section In Watts:
0.75 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
5.0 to 5.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
07397-37-815130 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
5 turret
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig: