NSN 5905-00-117-7927

Section Quantity:

125.0 single section

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-117-7927

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.000 inches
Mounting Bushing Length:
0.500 inches
Body Length:
1.875 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

NSN 5905-00-117-7927

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0/+70.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -2.0/+2.0 ohms single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Continuous motion **Tap Location From Ccw Terminal Per Section In Ohms:** 5000.0 single section **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 4 turret Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: