Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-119-9094

# Section Quantity:

1

Body Style:

Cylindrical

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.335 inches

#### **Body Length:**

0.250 inches

#### Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

300.0

#### **Terminal Location:**

Rear end

# Mounting Method:

Mounting Method

Terminal

#### **Electrical Resistance Per Section:**

200.0 ohms single section

## Rotary Actuator Travel In Angular Deg:

300.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

#### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

#### Power Dissipation Rating Per Section In Watts:

1.25 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

#### Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

# Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

---

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0