NSN 5905-00-122-7826

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-122-7826

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Shaft Diameter:
0.1248 inches
Mounting Bushing Length:
0.310 inches
Body Length:
1.457 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.50 inch-ounces
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25 to 0.25 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Resistance Tolerance Per Section In Percent:
-3.0 to 3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear

NSN 5905-00-122-7826

Precision Wire Wound Variable Resistor - Page 2 of 2



Ambie	nt Te	mpuratu	re In D	eg Ce	Isius F	Per S	ection	At Full	Rated	Power:

40.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0