## NSN 5905-00-122-8550

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-122-8550

| Electrical Resistance: 221.000 kilohms  Resistance Tolerance In Percent: -0.500 to 0.500  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0  Inclosure Method: Encapsulated  Terminal Type: |
|---|
| 221.000 kilohms  Resistance Tolerance In Percent: -0.500 to 0.500  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0  Inclosure Method: Encapsulated Terminal Type:                         |
| Resistance Tolerance In Percent: -0.500 to 0.500  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0  Inclosure Method: Encapsulated Terminal Type:  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0 to 145.0  Inclosure Method:  Encapsulated  Terminal Type:   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0 to 145.0  Inclosure Method:  Encapsulated  Terminal Type:   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type:   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0 to 145.0  Inclosure Method:  Encapsulated  Terminal Type:   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type:   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type:   |
| -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type:  |
| Inclosure Method:  Encapsulated  Terminal Type:   |
| Encapsulated Terminal Type:   |
| Terminal Type:  |
|   |
| Wire look   |
| Wire lead   |
| Reliability Indicator:  |
| Not established   |
| Body Diameter:  |
| 0.250 inches  |
| Body Length:  |
| 0.500 inches  |
| Power Dissipation Rating In Watts:  |
| 0.150 free air  |
| Style Designator:   |
| Axial terminal each end   |
| Test Data Document:   |
| 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format  |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental   |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A001a0  |